



- AC leakage current meter MODEL: DCM-040
1. AC resolution: 10 μ A
 2. Hook diameter: 30mm
 3. Maximum/minimum value and reading value lock
 4. AC current range: 40mA, 400mA, 4A, 40A, 60A

specification (23°C \pm 5°C)

ACA 0-40mA	10 μ A	\pm 1% \pm 3 digit	\pm 2.0% \pm 5 digit (40~1KHz)
ACA 0-400mA	100 μ A	\pm 1% \pm 3 digit	\pm 2.0% \pm 5 digit (40~1KHz)
ACA 0-4A	1mA	\pm 1% \pm 3 digit	\pm 2.0% \pm 5 digit (40~1KHz)
ACA 0-40A	10mA	\pm 1% \pm 3 digit	\pm 2.0% \pm 5 digit (40~1KHz)
ACA 0-60A	0.1A	\pm 1.5% \pm 5 digit	\pm 2.5% \pm 5 digit (40~1KHz)
ACA 0-100A	0.1A	\pm 3% \pm 5 digit	\pm 2.5% \pm 5 digit (40~1KHz)
ACV 0-400V	0.1V	\pm 1.5% \pm 2 digit	\pm 2.0% \pm 4 digit (40~1KHz)
Ω -400 Ohm	0.1 Ohm	\pm 1.0% \pm 2 digit	Beef if < 40 Ω (approx.)

• General specifications:

- o Hook size: max. approx. 30mm
- o Battery type: AA, 1.5V
- o Display: 3 3/4 LCD with analog segment graph
- o Range selection: Manual
- o Undervoltage warning:
- o Sampling rate: 2 times per second (digital)
- o 20 times per second (analogous to line segment graph)
- o Operating temperature and humidity: -10°C to 50°C/less than 85% (relative humidity)
- o Storage temperature and humidity: -20°C to 60°C/less than 75% (relative humidity)
- o Dimensions: 210mm (L) x 62mm (W) x 35.6mm (H)
- o Weight: 200 g (including battery)
- o Accessories: belt x 1, instruction manual x 1, 1.5V battery x 2